U

said terminal has an electrical conductivity equal to or greater than that of said resistor element, and

said terminal has a groove of a width fittable to said resistor element, and [being made of metal having electrical conductivity greater than that of said resistor element, and having a groove of a width fittable to said resistor element];

[wherein] said resistor element and said terminal are electrically connected by inserting said resistor element into said groove with a third metal inbetween.

28. (Twice amended) A method for manufacturing a low-resistance resistor comprising:

forming a resistor element made of a metal sheet, said resistor element having a shape adjusted to obtain a predetermined resistance;

forming a metal terminal having a groove;

fitting said terminal to both ends of said resistor element; and electrically connecting said resistor element and said terminal; wherein a third metal layer is formed on at least one of [at least]

a) a connecting portion of said resistor element, and [at least]



## b) a connecting portion of said terminal before fitting said terminal to said resistor element.

Respectfully Submitted

Lawrence E. Ashery, Reg. No. 34,518 Christopher I. Halliday, Reg. No. 42,621

Attorneys for Applicants

LEA/ap Dated: May 31, 2000 Suite 301, One Westlakes, Berwyn P.O. Box 980 Valley Forge, PA 19482-0980 (610) 407-0700

The Assistant Commissioner for Patents is hereby authorized to charge payment to Deposit Account No. 18-0350 of any fees associated with this communication.

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231 on: